


S22-P



Ordering dimensions in blue

Surface roughness $R_{t\max}$ R_a

Sliding surface $\leq 2,5 \mu\text{m}$ $0,1\text{--}0,5 \mu\text{m}$

Bottom of groove $\leq 6,3 \mu\text{m}$ $\leq 1,6 \mu\text{m}$

Groove face $\leq 15 \mu\text{m}$ $\leq 3 \mu\text{m}$

Bearing area: 50–95% and a cutting depth of $0,5 R_z$ based on $C_{ref} = 0\%$

Standard dimensions

d	D	L	$R_{t\max}$	c	maximal radial extrusion gap			
f8	H10	+ 0,2			20 bar	100 bar	200 bar	400 bar
over	incl.							

* Extrusion gap values shown above are valid for a temperature of 70°C , higher temperatures require lower values.
Standard: type 2

Ordering example

Profile

d x D x L [mm]

Sealing material / Support ring

Rod Seal S22-P

100 x 115 x 10

ECOPUR / SKF Ecotal



Operating parameters

Material Seal	Support ring	Temperature		Speed ¹⁾ max	Pressure ²⁾ max
		from	to		
-		°C		m/s	bar (MPa)
■ ECOPUR			-30		
■ H-ECOPUR	■ SKF Ecotal	-20		0,5	
■ T-ECOPUR	■ SKF Ecomid ³⁾	-40	+100		400 (40)
■ S-ECOPUR		-20		0,7	

IMPORTANT NOTE: The stated operating conditions represent general indications. It is recommended not to use all maximum values simultaneously.

¹⁾ Surface speed limit values are valid only in the presence of a lubrication film.

²⁾ Pressure ratings depend on the size of the extrusion gap.

³⁾ D ≤ 260 mm → SKF Ecotal, D > 260 mm → SKF Ecomid.

© ECOPUR and SKF are registered trademarks of the SKF Group

© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB SE/P8 11935 EN · March 2012

